







| Type | Description / Technical data | Order No. | Photo / Datasheet No. |
|------------|---|-----------|---|
| MCS-AY-Q14 | <p>Proximity (contactless) card reader</p> <p>Vandal & Water resistant, fully sealed reader for outdoor and indoor applications. Metal silver housing with LED & buzzer indicator, back-tamper function. Reading range: up to 65mm; Operating range: -30 ~ +65 °C; Current consumption: standby 35mA / reading 110mA; Dimensions (HxWxD): 120x76x27 mm; Ideal for special applications.</p> | 103.0101 |  |
| MCS-AY-Q64 | <p>Proximity (contactless) reader + Keypad (buttons)</p> <p>Vandal & Water resistant, fully sealed reader & keypad for outdoor and indoor applications. Metal silver housing with LED & buzzer indicator, back-tamper function. Reading range: up to 65mm; Operating range: -30 ~ +65 °C; Current consumption: standby 40mA / reading 130mA; Dimensions (HxWxD): 120x76x27 mm; Ideal for special applications.</p> | 103.0201 |  |
| MCS-AY-Q65 | <p>Proximity (contactless) reader + Keypad (piezoelectric)</p> <p>Vandal & Water resistant, fully sealed reader & keypad for outdoor and indoor applications. Metal silver housing with LED & buzzer indicator, back-tamper function. Reading range: up to 65mm; Operating range: -30 ~ +65 °C; Current consumption: standby 40mA / reading 130mA; Dimensions (HxWxD): 120x76x27 mm; Ideal for special applications.</p> | 103.0301 |  |
| MCS-AY-Q54 | <p>Keypad PIN reader (buttons)</p> <p>Vandal & Water resistant, fully sealed keypad reader for outdoor and indoor applications. Metal silver housing with LED & buzzer indicator, back-tamper function. Operating range: -30 ~ +65 °C; Current consumption: standby 40mA / reading 130mA; Dimensions (HxWxD): 120x76x27 mm; Ideal for special applications.</p> | 103.0401 |  |
| MCS-AY-T55 | <p>Keypad PIN reader (piezoelectric)</p> <p>Vandal & Water resistant, fully sealed keypad reader for outdoor and indoor applications. Metal silver housing with LED & buzzer indicator, back-tamper function. Operating range: -30 ~ +65 °C; Current consumption: standby 40mA / reading 130mA; Dimensions (HxWxD): 120x65x27 mm; Ideal for special applications.</p> | 103.0501 |  |
| MCS-AY-S55 | <p>Keypad PIN reader (piezoelectric)</p> <p>Vandal & Water resistant, fully sealed keypad reader for outdoor and indoor applications. Metal silver housing with LED & buzzer indicator, back-tamper function. Operating range: -30 ~ +65 °C; Current consumption: standby 40mA / reading 130mA; Dimensions (HxWxD): 150x42x27 mm; Ideal for special applications.</p> | 103.0601 |  |