







Section 5 ACCESS CONTROL READERS
Indoor only

Type	Description / Technical data	Order No.	Photo / Datasheet No.
MCS-AY-D12	Proximity (contactless) card reader Proximity reader for indoor applications. White plastic housing with LED & buzzer indicator, back-tamper function. Reading range: up to 100mm; Operating range: 0 ~ +45 °C; Current consumption: standby 35mA / reading 50mA; Dimensions (HxWxD): 122x75x24 mm; For indoor application only.	105.0101	
MCS-AY-C12	Proximity (contactless) card reader Proximity reader for indoor applications. White plastic housing with LED & buzzer indicator, back-tamper function. Reading range: up to 100mm; Operating range: 0 ~ +45 °C; Current consumption: standby 35mA / reading 50mA; Dimensions (HxWxD): 122x75x24 mm; For indoor application only.	105.0201	
MCS-MSR-262	Magnetic Stripe Slot Reader Magnetic stripe reader for magnetic stripe cards. Black plastic housing with LED indicator. Operating range: 0 ~ +45 °C; Current consumption: 30mA; Dimensions (HxWxD): 100x31x32 mm; For indoor application only.	105.0301	
MCS-BCR-250	Barcode Slot Reader Barcode slot reader in black plastic housing with LED indicator. Operating range: 0 ~ +45 °C; Current consumption: 38mA; Dimensions (HxWxD): 100x31x32 mm; For indoor application only.	105.0401	
MCS-PCR-230	Proximity (contactless) FRID Code Verifier Proximity reader Code Verifier for defining and verifying the Proximity (contactless) cards and tags. Keyboard PS2 interface for PC with "Y" connection cable for PC Keyboard & Code Verifier to PC. White plastic housing with LED & buzzer indicator. Reading range: up to 100mm; Operating range: 0 ~ +45 °C; Current consumption: 300mA; Dimensions (HxWxD): 134x38x65 mm; For indoor application only.	105.0501	
MCS-MSR-400	Magnetic Stripe Code Verifier Magnetic stripe slot verifier for defining and verifying the magnetic stripe cards. Keyboard PS2 interface for PC with "Y" connection cable for PC Keyboard & Code Verifier to PC. White plastic housing with LED & buzzer indicator. Operating range: 0 ~ +45 °C; Current consumption: 80mA; Dimensions (HxWxD): 170x42x44 mm; For indoor application only.	105.0601	
MCS-BCR-431	Barcode Code Verifier Barcode verifier for defining and verifying the barcodes cards. Keyboard PS2 interface for PC with "Y" connection cable for PC Keyboard & Code Verifier to PC. White plastic housing with LED & buzzer indicator. Operating range: 0 ~ +45 °C; Current consumption: 80mA; Dimensions (HxWxD): 170x42x44 mm; For indoor application only.	105.0701	